Fieldpiece

曼 <u>US Eng</u>-Q

Job Link[®] System Products

Company

Register a Product

Search Here

Track Order

Home > Products > Job Link[®] System > Job Link[®] System Probes > **JL3KH6**



View and Download High Resolution Images

JL3KH6 - Job Link[®] System Charge & Air Kit

Contact Us

Wireless Range of 350' Plus

Where to Buy

Take a full system snapshot quickly and easily with the JL3KH6 Charge and Air Test Kit. This kit consists of 2 pressure probes, 2 pipe clamps, and 2 psychrometers in a quick access padded case. All measurements can be sent up to 350' away directly to your mobile device with the Job Link® System mobile app. Each tool is designed for agility and speed. The pressure probes fit into tight spaces. The pipe clamps use the new Rapid Rail[™] sensor design delivering accuracy, speed, and agility, even on the most awkward pipe configurations. The psychrometers' flexible narrow probes and configurable magnet make it easy to measure supply plenums, ducts, and elevated registers. Do more with Job Link probes!

- Directly connects to mobile device with Job Link System App
- Fast accurate temps with new Rapid Rail technology
- Pressures auto calibrate at any elevation
- Configurable psychrometers with flexible probe and sliding magnet







	Overview	Specifications	Users Manuals	Print Review					
Wireless Range: 350 feet or more									

8.07	
Reformation	Supply hr
42497.6	58.2
Superior .	The of the burn
75.7 Pry Pull	54.5
65.1	53.5
Wet theil	Well Public
	v.
	rant Side
Sector Line	Linguist Line
124.3	297.3
Antones	displayer.
42.5	95.2
Vapit-Samerror	Labora gaunament
54.7 -	
Everyone promy	Corporate 1
12.2	15.5
15.5	15.0
THERE MANAPPEND	T-LINE BUDGERAS
	TXWEXY
7581 Tall#	Mehavinik Deble k
The State	104130

 $\bullet \bullet \bullet \bullet$

Wireless Frequency: 2.4 GHz Battery: 2 x AAA (included) Battery Life: 150 hrs typical alkaline Auto Power Off (APO): 2 hrs (can be disabled) Minimum Device Requirement: BLE 4.0 devices running iOS® 7.0 or AndroidTM 5.0

Job Link Pressure Probe - JL3PR Connector Type: 45° Standard 1/4" NPT female flare Best Accuracy: ±1 psig (±7 kPa) Measurement Range: 0 to 580 psig (0 to 4000 kPa) Maximum Overload: 800 psig (5500 kPa) Water Resistant: Designed to IP55



Recommended Products



LOREM IPSUM





LOREM IPSUM

					00001
	Enter Your Email Address		Subscribe Now		
	Products	In The Know	Company	Information	
Fieldpiece	Job Link [®] System	FAQs	News	Site Map	
Fieldpiece	A/C Analysis	Get Support	Careers	Privacy & Terms	
	Charging	Distributors	Success Stories	GDPR Compliance	0
Tools HVACR Pros Trust	Meters	Track Your Order	About Fieldpiece	CCPA Compliance	
	Temperature/RH	Request a Repair	Patents		
	Leak Detectors	Register a Product	Where to Buy		
	Air Flow	Partners' Resources	Contact Us		
	Combustion	Subscribe for Updates			
	Bags				
	Pocket Tools				
	Leads				
	© 2020 Fieldpiece Instru	uments, Inc. All rights reserved.			