

# TEK-Mate®

## REFRIGERANT LEAK DETECTOR

### Find leaks fast.

Affordable price, simple operation, and reliable performance make TEK-Mate the refrigerant leak detector of choice for thousands of technicians. See for yourself why TEK-Mate is the #1 refrigerant leak detector for many HVAC/R technicians.



EN14624

2 x D



### ADVANTAGES

- Sensitivity of 0.25 oz. (7 g)/year
- Detects all CFCs, HCFCs, HFCs, and HFOs
- Proven heated diode sensor for reliable leak checking
- No false alarms from soap solutions
- Runs on two D-cell batteries
- Rugged carrying case included

### SPECIFICATIONS

Includes	TEK-Mate Heated diode sensor Two D-size alkaline batteries Spare filters Carrying case
Compatible refrigerants	R22, R32, R134a, R404a, R407c, R410a, R422b, R448a, R449a, R452a, R452b, R507 (AZ50), R1234yf/ze and more
Minimum sensitivity	0.25 oz./yr. (7 g/yr.)
Sensitivity per EN14624	0.07 oz./yr.(2 g/yr.)
Power source	Two D-size alkaline batteries
Battery life	16 hours
Weight	1.54 lb. (700 g)
Certifications	EN14624:2020 A2L certified CE, UKCA
Probe length	15 in. (38 cm)
Warranty	Two-year over-the-counter

### ORDERING INFORMATION

TEK-Mate 705-202-G1

#### Accessories and Replacement Parts

TEK-Check R134a reference leak	703-080-G10
TEK-Check R1234yf reference leak	703-080-G12
Sensor	703-020-G1
Filters	705-600-G1
Carrying case	705-700-G1



LEARN MORE  
HERE!